

SUMMIT TRACTORS TX25H

Optional Backhoe



FREQUENTLY ASKED QUESTIONS

Q. WHO MAKES THE TRACTOR?

A. Summit Tractors manufactures its own tractors, unlike many other compact tractor brands that may be rebranded versions of another tractor. The Goodyear tires & wheels and backhoe are made in the USA.

Q. WHERE DO I GET IT SERVICED?

A. Summit Tractors has partnered with Service Dealers located near every location that Summit Tractors are sold. Providing quality service is our top priority

Q. WHAT IS THE WARRANTY?

A. Summit Tractors have the industry's longest full machine warranty at 3 years or 2000 hours and a limited powertrain warranty of 7 years or 3000 hours

Q. HOW DOES THIS TRACTOR COMPARE TO OTHER NAME BRANDS?

A. Summit Tractors have more standard features than any tractor in its HP class, with the highest levels of performance & quality

Q. DO YOU OFFER FINANCING?

A. Yes, no down payment financing is available for up to 84 months.



APPLY NOW

HAVE QUESTIONS?

Call or Text 770-209-3390

Email: support@summittractors.com

FULLY LOADED READY TO GO TO WORK™

- 24.7 HP Mitsubishi EPA Tier 4 Diesel Engine
- 18 PTO HP, Rear 540 RPM, Mid 2100 RPM
- Hydrostatic Transmission with Side-By-Side Pedals
- One Set Self-Canceling Detent Rear Hydraulic Remotes
- Cruise Control
- 4WD With Differential Lock
- RimGuard™ Liquid Tire Ballast Rear Tires
- 3rd Function Diverter Valve (Grapple Ready) with Integrated Joystick
- Projector Headlamps and Rear Work Light
- Skid-Steer Quick Attach and Self-Leveling Loader
- 7-Point Trailer Connector and Front Tow Hook
- Goodyear All Condition R14T Tires
- Foldable and Removeable Side-View Mirrors
- Category 1 3-Pt Hitch with Swinging and Bar Drawbars
- Premium Adjustable Suspension Seat



THE INDUSTRY'S LONGEST FULL MACHINE WARRANTY

Full Machine: 3 years or 2000 Hours

Limited Powertrain: 7 years or 3000 Hours



A Donation is Made by Summit Tractors for Every Tractor Sold



DOWNLOAD THE MOBILE APP
AND GET CONNECTED



SUMMITTRACTORS.COM



SCAN ME

SUMMIT TRACTOR, LOADER & BACKHOE STANDARD FEATURES & SPECIFICATIONS

ENGINE

Engine Manufacturer	Mitsubishi
Engine Type	Natural Aspiration
Engine HP-Gross	24.7 (18.4)
PTO HP (kw)	18 (13.4)
Rated engine speed	2500
Number of cylinders	3
Displacement-cu.in. (cc)	80.42 (1318)
Cooling System & Air Cleaner Type	Liquid, Dual Element
Alternator	12V42A
Starting Aid	Glow Plug
Fuel System Type	Indirect Fuel Injection
Fuel Tank, U.S. gal. (l)	6.9 (26)

POWERTRAIN

Transmission type	2-Range Hydrostatic
Forward/Reverse Foot Control	Side-by-Side Pedals
Cruise Control	Standard Electronic
Max Traveling Speed, mph (km/h)	11.32 (18.22)
Brakes	Wet Disc
Steering	Hydraulic

HYDRAULIC SYSTEM

Pump Type	Open Center
Max Total flow gpm (L/Min)	6.6 (24.9)
Category, 3 Point Hitch	Category 1 Standard
3 Point Hitch Lift Capacity, lb (kg)	1322 (600)
At 24 inches behind link ends, lb (kg)	1168 (530)
Lift Control type	Position Control
Rear Hydraulic Remote Valves	Standard
3rd Function Diverter Valve (Grapple Ready)	Standard

PTO

PTO Type	Independent
PTO Control	Electric/Hydro
PTO Rear (rpm)	540
PTO Mid (rpm)	Standard - 2100
PTO Shaft Diameter in. (mm)	1 3/8 (35)

OTHER

Two Drawbars - Cross-Type and Swinging	Standard
Front Tow Hook	Standard
Entry Step Both Sides	Standard
Hood Material	Metal
RimGuard Liquid Tire Ballast (Rears)	Standard
Projector Headlights & Rear Work Light	Standard

DIMENSIONS

Overall Length, in. (mm) Front to End of 3-pt.	154 (3911)
Overall Width, in. (mm)	54 (1371)
Wheelbase, in. (mm)	61.8 (1569.72)
Height to Top of ROPS, in. (mm)	92.12 (2339.84)
Min. Ground Clearance, in. (mm)	9.6 (245) - Front Axle
Total Weight, lb (kg) Without Loader & Tire Ballast	2513 (1139.8)
Total Weight, lb (kg) With Loader & Tire Ballast	3600 (1632.9)

STANDARD TIRES

Front	USA Goodyear R14T 23x8.50-12
Rear	USA Goodyear R14T 12-16.5

OPERATOR STATION

Roll Over Protection Structure (ROPS) Type	Folding
High Back Seat With Backrest Extension	Standard
Folding & Angle-Adjustable Armrests	Standard
Retractable Seat Belt	Standard
Seat Cover Type	Weatherproof Coated PVC
Side View Mirrors	Standard - Hand Adjustable, Removeable
Dial by Operator Weight Seat Suspension Adjustment	Standard
Heavy Duty Rubber Floor Mat	Standard
Entry Assist Steps & Grab Rails Both Sides	Standard
12V Power Outlet	Standard
Entry Assist Steps & Grab Rails	Both Sides Standard
12V Power Outlet & Cup Holder	Standard

FRONT-END LOADER

Model	LX85
Mechanical Self-Leveling	Standard
Breakout Force at Pivot Pin, lb. (kg)	1477 (670)
Maximum Lift Height to Bucket Pivot Pin, in. (mm)	83(2108)
Lift Capacity to Maximum Height at Pivot Pin, lb. (kg)	1234 (559)
Dumping Clearance, in. (mm)	61 (1540)
Bucket Width, in. (mm)	50 (1270)
Total weight loader with bucket, lb.(kg)	573 (260)
Weight of bucket, lb.(kg)	176 (80)
Bucket connection type (ability to swap out bucket for a range of attachments)	Skid Steer Quick Attach (SSQA)
Bucket level indicator (BLI)	Standard

BACKHOE

Model	BHX76
Operator Seat	Independent
Mechanical Thumb	Standard
Tractor Attachment Type	Full Subframe Mount - Removeable
3-Pt hitch to enable implement use when BH is removed	Standard
Bucket Sizes	12" Standard - Optional 8", 16"
Maximum Digging Depth	78"
Swing Arc (degrees)	148
Reach From Center Line of Swing Point	109"
Transport height (maximum)	72"
Loading reach (bucket at 60 degrees)	35"
Stabilizer spread, down position	74"
Stabilizer spread, up position	59"
Bucket cylinder digging force	2270 lbs.
Dipperstick cylinder digging force	1248 lbs.

*This brochure is for descriptive purposes only. Summit Tractors reserves the right to change the stated specifications and information without notice. Summit Tractors disclaims all representations and warranties, express or implied, and any liability from the use of this brochure. For complete warranty, safety and product information, visit www.summittractors.com and download the operator manual. Horsepower (HP) and other specifications are based on various standards or recommended practices. For your safety, Summit Tractors strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

FOR MORE INFORMATION VISIT SUMMITTRACTORS.COM